







Pin Hex - Countersunk Self Tapping Screws - A2 Stainless Steel





Head Dimensions

\bigcirc		SEEL IAITING SOLENS						
	PIN HEX	No. 6	No. 8	No. 10	No. 12	No. 14		
	DIMENSIONS	3.5mm	4.2mm	4.8mm	5.5mm	6.3mm		
COUNTERSUNK HEAD	\square	6.6	7.9	9.3	10.4	12.4		
		2.1	2.5	3.0	3.4	3.8		


Material and Finish

Material:	A2 Stainless Steel
Heat Treatment:	None
Finish:	Passivated

Part Numbers

	LENGTH	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	2"	2 ¹ /2"	DRIVER	
GAUGE		9.5mm	13mm	16mm	19mm	25mm	32mm	38mm	50mm	63mm	SIZE	
6	3.5mm	PHCS 06C-M	PHCS 06D-M	PHCS 06E-M	PHCS 06F-M	PHCS 06G-M		PHCS 06I-M			HM2	
8	4.2mm		PHCS 08D-M	PHCS 08E-M	PHCS 08F-M	PHCS 08G-M	PHCS 08H-M	PHCS 08I-M	PHCS 08J-M		HM2.5	
10	4.8mm		PHCS 10D-M	PHCS 10E-M	PHCS 10F-M	PHCS 10G-M	PHCS 10H-M	PHCS 10I-M	PHCS 10J-M	PHCS 10K-M	HM3	
12	5.5mm				PHCS 12F-M	PHCS 12G-M	PHCS 12H-M	PHCS 12I-M	PHCS 12J-M		HM4	
14	6.3mm				PHCS 14F-M	PHCS 14G-M	PHCS 14H-M	PHCS 12I-M	PHCS 12J-M		HM4	

Addtional Information



Every effort has been made to ensure the accuracy of information provided in this catalogue. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.