



**Reduced CSK Head
- Plain Body - Imperial Hole**



● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall Length
METRIC SIZES						
M3	0.5-1.5	4.8	4.8	5.4	0.4	9.0
M4	0.5-2.0	6.4	6.4	7.1	0.5	10.5
M5	0.5-3.0	7.2	7.2	8.1	0.6	12.0
M6	0.5-3.5	9.6	9.6	10.3	0.6	15.0
M8	0.7-3.8	10.6	10.6	11.5	0.6	16.0
M10	1.0-5.0	12.8	12.8	13.9	0.7	20.0
UNIFIED SIZES						
6-32	0.5-2.0	6.4	6.3	7.2	0.5	10.4
8-32	0.5-2.0	6.4	6.3	7.1	0.5	10.4
10-24	0.5-3.3	7.2	7.1	8.1	0.5	12.0
10-32	0.5-3.3	7.2	7.1	8.1	0.5	12.0
1/4-20	0.8-4.2	9.6	9.5	10.5	0.5	15.0
5/16-18	1.0-5.0	12.7	12.7	13.9	0.6	19.0
3/8-16	1.0-5.0	12.7	12.7	13.9	0.7	19.0

**Reduced CSK Head
- Knurled Body - Imperial Hole**



The reduced countersunk head style offers near flush installation without any extra hole preparation. The knurled body type has extra resistance to turning forces especially when installed in softer materials.

● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Diameter	Body Diameter	Head Diameter	Head Thickness	Overall Length
M3	0.5-1.5	4.8	4.7	3.17	3.17	9.0
M4	0.5-2.0	6.4	6.3	3.17	3.17	10.5
M5	0.5-3.0	7.2	7.1	3.17	3.17	12.0
M6	0.5-3.5	9.6	9.5	3.17	3.17	15.0
M8	0.7-3.8	10.6	10.5	3.17	3.17	16.0

**Reduced CSK Head
- Knurled Body - Metric Hole**



● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-2.0	5.0	4.9	6.0	0.5	9.0
M4	0.5-2.0	6.0	5.9	7.0	0.5	11.3
M4	2.0-4.0	6.0	5.9	7.0	0.5	13.0
M5	0.5-3.0	7.0	6.9	8.0	0.5	12.0
M5	2.0-4.0	7.0	6.9	8.0	0.5	13.0
M6	0.5-3.0	9.0	8.9	10.0	0.6	14.0
M6	2.5-4.5	9.0	8.9	10.0	0.6	16.0
M8	0.5-3.8	11.0	10.9	12.0	0.6	17.3
M8	3.0-5.0	11.0	10.9	12.0	0.6	18.5
M10	0.7-3.5	12.0	11.9	13.0	0.7	19.5
M10	0.7-3.5	13.1	12.9	14.0	0.8	21.0
M10	3.5-6.0	13.1	12.9	14.0	0.8	23.5
M12	1.0-3.5	16.1	15.9	17.0	1.0	24.2

**Reduced CSK Head
- Half Hex Body - Imperial Hole**



Blind rivet nuts with a hexagon body fit into hexagon holes and eliminate the potential problem of rivet nuts turning after installation. The reduced countersunk head style offers near flush installation in thin materials without any extra hole preparation. The half-hex body style assists easy entry into the prepared holes.

● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.0	6.4	6.35	7.0	0.4	10.4
M5	0.5-3.0	7.2	7.1	8.1	0.5	12.0
M6	0.5-3.0	9.6	9.5	10.5	0.5	14.5
M8	0.7-3.2	10.7	10.5	11.5	0.6	16.0


**Reduced CSK Head - Half Hex Body
- Metric Hole**



● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M3	0.5-1.5	5.1	4.9	6	0.5	9.3
M3	1.5-2.5	5.1	4.9	6	0.5	10
M4	0.5-2.0	6.1	5.9	7	0.5	12
M5	0.5-3.0	7.1	6.9	8	0.5	13
M6	0.5-3.0	9.1	8.9	10	0.6	16
M8	0.7-3.0	11.1	10.9	12	0.6	16.5
M10	0.8-3.5	13.1	13	14	0.8	20

**Reduced CSK Head
- Full Hex Body**



● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.5	6.1	6	7	0.5	11
M4	2.0-4.0	6.1	6	7	0.5	12.2
M5	0.5-3.0	7.1	7	8	0.5	14.5
M5	2.0-4.5	7.1	7	8	0.6	15
M6	0.6-3.5	9.1	9	10	0.6	16
M6	3.0-5.5	9.1	9	10	0.6	18
M8	0.7-4.0	11.1	11	12	0.6	18
M8	3.0-5.5	11.1	11	12	0.6	19
M10	1.0-3.5	13.1	13	14.5	1	20
M10	3.0-6.0	13.1	13	14.5	1	25
M12	1.0-4.0	16.1	16	17.5	1	25

**Reduced CSK Head - Plain Body
- Imperial Hole - Closed End**




Closed end rivet nuts prevent the ingress of moisture and contamination into a component and are available in all three head styles. If sealing the nut is critical then a dry under head sealant can be applied. The closed end rivet nuts can also be used to prevent too long a screw being inserted into the part.

● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.0	6.4	6.4	7.2	0.5	15
M5	0.5-3.0	7.2	7.1	8.1	0.5	20.2
M6	0.7-3.0	9.6	9.5	10.5	0.6	23.5
M8	0.7-3.5	10.6	10.5	11.5	0.6	23

**Reduced CSK Head - Knurled Body
- Metric Hole - Closed End**



● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.0	6	5.9	7	0.5	15
M4	2.0-4.0	6	5.9	7	0.5	16.5
M5	0.5-2.5	7	6.9	8	0.5	16.5
M5	2.0-4.0	7	6.9	8	0.5	18
M6	0.5-3.0	9	8.9	10	0.6	20.5
M6	2.5-5.0	9	8.9	10	0.6	22
M8	0.7-3.0	11	10.9	12	0.6	23
M8	3.0-5.0	11	10.9	12	0.6	24.5
M10	1.0-3.0	13	12.9	14	0.7	24.5
M10	3.5-6.0	13	12.9	14	0.7	26

**Reduced CSK Head - Full Hex Body
- Metric Hole - Closed End**



Other options:
**Half Hex Body
Longer Grip Range**

Please contact our sales department for further details.

● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.0	6.1	6	6.9	0.5	16
M5	0.5-3.0	7.1	7	8	0.5	20
M6	0.5-3.0	9.1	9	10	0.5	22
M8	0.7-3.0	11.1	11	12	0.6	25.5

Flange Head - Plain Body



The flange head style is suitable for load bearing applications as the larger diameter head reinforces the hole and increases push-out resistance. The head can also be used as a spacer; the knurled body type provides extra resistance to turning especially when installed in softer materials.

● **STEEL ZINC Cr3 FINISH**

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.5	6	5.9	9	0.8	11.5
M5	0.5-2.5	7	6.9	10	1	13
M6	0.5-3.0	9	8.9	12.5	1.3	15.5
M8	0.7-4.0	11	10.9	15	1.5	18
M10	1.0-3.5	12	11.9	16	1.6	19
M10	1.0-5.0	13	12.9	17	1.7	19.3
M12	1.0-4.0	16.1	15.9	23	2	27

Flange Head - Knurled Body



Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M3	0.5-2.0	5	4.9	8	0.8	10
M3	2.5-4.0	5	4.9	7	0.9	11.5
M4	0.5-2.5	6	5.9	9	1	11.6
M4	3.0-5.5	6	5.9	9	1	14
M5	0.5-2.5	7	6.9	10	1	13
M5	3.0-5.5	7	6.9	10	1	16
M5	5.5-8.0	7	6.9	10	1	19
M6	0.5-3.0	9	8.9	12.5	1.5	16
M6	3.0-5.5	9	8.9	12.3	1.3	19.5
M6	5.5-8.0	9	8.9	12.3	1.5	21
M8	0.7-3.0	11	10.9	16	1.5	18.5
M8	3.0-5.5	11	10.9	16	1.5	21
M8	5.5-8.0	11	10.9	15	1.6	24
M8	8.0-10.5	11	10.9	15	1.6	25
M10	1.0-3.5	12	11.9	16	2	19
M10	3.0-6.0	12	11.9	16	2	24
M10	6.0-9.0	12	11.9	16	2	27
M10	9.0-12.0	12	11.9	16	2	30
M10	1.0-3.5	13	12.9	19	2	21
M10	3.5-6.0	13	12.9	19	2	23.5
M12	1.0-4.0	16	15.9	22	2.1	25
M12	4.0-7.0	16	15.9	22	2.1	28
M12	7.0-10.0	16	15.9	22	2.1	31

Flange Head - Full Hex Body



Other options:
Half Hex Body

Please contact our sales department for further details.

This style of rivet nut is suitable for applications where both high push-out and high torque-out performance are required.

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.5	6.1	6	9	0.8	11.2
M5	0.5-2.5	7.1	7	10	1	14
M6	0.5-3.0	9.1	9	13	1.3	15.5
M6	3.0-5.5	9.1	9	13	1.5	18
M8	0.7-3.5	11.1	11	16	1.5	18
M8	3.0-5.5	11.1	11	16	1.5	20.5
M10	1.0-4.0	13.1	13	19	2	22
M10	3.5-6.0	13.1	13	19	2	25.5
M12	1.0-4.0	16.1	16	23	2	27

Flange Head - Knurled Body - Closed End



● STEEL ZINC Cr3 FINISH

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M3	0.5-2.5	5	4.9	7	0.9	15
M3	2.5-4.0	5	4.9	7	0.9	16
M4	0.5-3.0	6	5.9	9	1	16
M4	3.0-5.5	6	5.9	9	1	19
M5	0.5-3.0	7	6.9	10	1	18.5
M5	3.0-5.5	7	6.9	10	1	21.5
M5	5.5-8.0	7	6.9	10	1	24.5
M6	0.5-3.0	9	8.9	12	1.5	21.5
M6	3.0-5.5	9	8.9	12	1.5	24
M6	5.5-8.0	9	8.9	12	1.5	26.5
M8	0.5-3.0	11	10.9	15	1.5	26
M8	3.0-5.5	11	10.9	15	1.5	28.5
M8	5.5-8.0	11	10.9	15	1.5	31
M8	8.0-10.5	11	10.9	15	1.5	33.5
M10	0.5-3.0	12	11.9	16	2	28
M10	3.0-6.0	12	11.9	16	2	33
M10	6.0-9.0	12	11.9	16	2	36
M10	9.0-12.0	12	11.9	16	2	39

Flange Head - Full Hex Body - Closed End



Other options:

Half Hex Body

Please contact our sales department for further details.

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.0	6.1	6	9	1	16
M5	0.5-3.0	7.1	7	10	1	20
M6	0.5-3.0	9.1	9	13	1.5	23
M8	0.5-3.0	11.1	11	16	1.5	26
M8	3.0-5.5	11.1	11	16	1.5	28.5
M10	0.8-3.5	13.1	13	19	2	33

Countersunk Head - Knurled Body



Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M3	1.5-3.5	5	4.9	7.5	1.5	11.5
M3	3.5-5.0	5	4.9	7.5	1.5	12.5
M4	1.5-3.5	6	5.9	8.5	1.5	12
M4	3.5-6.5	6	5.9	8.5	1.5	15
M5	1.5-4.0	7	6.9	9.5	1.5	13
M5	4.0-6.5	7	6.9	9.5	1.5	16
M5	6.5-9.0	7	6.9	9.5	1.5	18.5
M6	1.5-4.0	9	8.9	11.5	1.5	15.5
M6	4.0-6.5	9	8.9	11.5	1.5	18
M6	6.5-9.0	9	8.9	11.5	1.5	20.5
M8	1.7-4.5	11	10.9	13.5	1.5	18.5
M8	4.0-6.5	11	10.9	13.5	1.5	21
M8	6.5-9.0	11	10.9	13.5	1.5	23.5
M10	2.0-4.5	12	11.9	14.5	1.7	21
M10	4.5-7.5	12	11.9	14.5	1.7	24
M10	7.5-10.5	12	11.9	14.5	1.7	27
M12	2.0-4.5	16	15.9	19	1.9	24.5
M12	4.5-7.5	16	15.9	19	1.9	27.5
M12	7.5-10.5	16	15.9	19	1.9	31

Split Body Rivet Nuts




The split body rivet nuts are ideal for use in plastic materials, thin sheet and hollow sections where very high pull-out forces are required. The 4 legs expand behind the parent material to provide a large load-bearing area.

● STEEL ZINC Cr3 FINISH

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.1-5.0	8	8	12	1.6	17
M4	5.0-10.0	8	8	12	1.6	22
M5	0.1-5.0	10	10	14	1.6	18
M5	5.0-10.0	10	10	14	1.6	23
M6	0.1-5.0	12	12	16	1.6	18
M6	5.0-10.0	12	12	16	1.6	23
M8	0.1-8.0	15	15	18	1.8	20.5
M8	5.0-12.0	15	15	18	1.8	25.5


Blind Rivet Bolts



● STEEL ZINC Cr3 FINISH

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M4	0.5-2.0	5.5	5.4	8	0.5	10
M4	2.0-3.0	5.5	5.4	8	0.5	10
M4	0.5-2.0	5.5	5.4	8	0.5	15
M4	2.0-3.0	5.5	5.4	8	0.5	15
M5	0.5-2.0	6.6	6.5	9	0.8	10
M5	2.0-3.5	6.6	6.5	9	0.8	10
M5	0.5-2.0	6.6	6.5	9	0.8	15
M5	2.0-3.5	6.6	6.5	9	0.8	15
M6	0.5-2.5	7.8	7.7	10	1	10
M6	2.5-4.0	7.8	7.7	10	1	10
M6	0.5-2.5	7.8	7.7	10	1	15
M6	2.5-4.0	7.8	7.7	10	1	15
M8	1.0-3.0	9.9	9.8	12	1.5	15
M8	3.0-5.0	9.9	9.8	12	1.5	15
M8	1.0-3.0	9.9	9.8	12	1.5	20
M8	3.0-5.0	9.9	9.8	12	1.5	20

Reduced CSK Head - Knurled Body - Imperial Hole



The reduced CSK head split body rivet nuts are ideal for use in soft or brittle materials such as plastic, paperboard and GRP. The 3 legs expand behind the parent material to provide a large footprint and excellent pull-out resistance.

● STEEL ZINC Cr3 FINISH

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M6	0.5-7.1	10.0-10.2	9.8	16.4	1.6	27.4
M6	7.1-12.7	10.0-10.2	9.8	16.4	1.6	33.3
M8	0.5-7.1	12.7-12.9	12.6	19.6	1.7	31.3
M8	7.1-12.7	12.7-12.9	12.6	19.6	1.7	37
M10	0.5-7.1	15.1-15.3	14.9	22.7	2.4	33.7

Countersunk Head - Knurled Body - Closed End



Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Diameter	Head Thickness	Overall Length
M3	1.5-3.5	5	4.9	7.5	1.5	16
M3	3.5-5.0	5	4.9	7.5	1.5	17
M4	1.5-4.0	6	5.9	8.5	1.5	17.5
M4	4.0-6.5	6	5.9	8.5	1.5	20
M5	1.5-4.0	7	6.9	9.5	1.5	20
M5	4.0-6.5	7	6.9	9.5	1.5	22.5
M5	6.5-9.0	7	6.9	9.5	1.5	25
M6	1.5-4.0	9	8.9	11.5	1.5	23
M6	4.0-6.5	9	8.9	11.5	1.5	25.5
M6	6.5-9.0	9	8.9	11.5	1.5	28
M8	1.5-4.0	11	10.9	13.5	1.5	27
M8	4.0-6.5	11	10.9	13.5	1.5	29.5
M8	6.5-9.0	11	10.9	13.5	1.5	32
M10	2.0-4.5	12	11.9	14.5	1.7	30
M10	4.5-7.5	12	11.9	14.5	1.7	33
M10	7.5-10.5	12	11.9	14.5	1.7	36
M12	2.0-4.5	16	15.9	19	1.9	34.5
M12	4.5-7.5	16	15.9	19	1.9	37.5
M12	7.5-10.5	16	15.9	19	1.9	40.5

**Reduced CSK Head
- Plain Body - Imperial Hole**




The reduced countersunk head style offers near flush installation without any extra hole preparation. The knurled body type has extra resistance to turning forces especially when installed in softer materials.

STAINLESS STEEL A2

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-1.5	4.8	4.7	5.5	0.5	9.2
M4	0.5-2.0	6.4	6.3	7	0.5	10.5
M5	0.5-3.0	7.2	7.1	8	0.5	12
M6	0.5-3.0	9.6	9.5	10.5	0.5	14.6
M8	0.5-3.0	10.6	10.5	11.5	0.5	16.2

**Reduced CSK Head - Knurled Body
Body - Metric Hole**



STAINLESS STEEL A2

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-2.0	5	4.9	6	0.5	9
M4	0.5-2.5	6	5.9	7	0.5	11
M4	2.5-4.0	6	5.9	7	0.5	12.5
M5	0.5-3.0	7	6.9	8	0.5	12
M5	3.0-4.5	7	6.9	8	0.5	13.5
M6	0.5-3.0	9	8.9	10	0.5	14
M6	3.0-5.0	9	8.9	10	0.5	16
M8	0.7-3.0	11	10.9	12	0.5	16
M8	3.0-5.5	11	10.9	12	0.5	18.5
M10	1.0-3.5	13	12.9	14.2	0.8	19
M10	3.5-6.0	13	12.9	14.2	0.8	21.5
M12	1.0-4.0	16	15.9	17.2	0.8	22.5

* This part (M12) has a smooth body.

Reduced CSK Head - Half Hex Body



STAINLESS STEEL A2

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-2.0	5.1	5	6	0.4	9
M3	2.0-3.2	5.1	5	6	0.4	9.5
M4	0.5-2.5	6.1	6	7	0.5	11
M4	2.5-4.0	6.1	6	7	0.5	12.5
M5	0.5-3.0	7.1	7	8	0.5	12
M5	3.0-4.5	7.1	7	8	0.5	13.5
M6	0.5-3.0	9.1	9	10	0.5	14
M6	3.0-5.0	9.1	9	10	0.5	16
M8	0.5-3.0	11.1	11	12	0.5	16
M8	3.0-5.0	11.1	11	12	0.5	18.5
M10	1.0-3.5	13.1	13	14.2	0.7	19

**Reduced CSK Head
- Closed End**



Closed end rivet nuts prevent the ingress of moisture and contamination into a component and are available in all three head styles. If sealing the nut is critical then a dry under head sealant can be applied. The closed end rivet nuts can also be used to prevent too long a screw being inserted and damaging the part.

STAINLESS STEEL A2

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia. Max	Head Thickness	Overall length
M3	0.5-2.0	5.1	5	6	0.5	13
M4	0.5-2.5	6.1	6	7	0.5	16
M5	0.5-3.0	7.1	7	8	0.5	18
M6	0.5-3.0	9.1	9	10	0.5	21
M8	0.5-3.0	11.1	11	12	0.5	23.5
M10	1.0-3.5	13.1	13	14.2	0.8	26.5

**Reduced CSK Head - Half Hex Body
Body - Closed End**



Blind rivet nuts with a hexagon body fit into hexagon holes and eliminate the potential problem of rivet nuts turning after installation. The reduced countersunk head style offers near flush installation in thin materials without any extra hole preparation.

STAINLESS STEEL A2

Thread Size	Grip Range	Hole Size AF	Body Size AF	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	7	0.5	16
M4	2.5-4.0	6.1	6	7	0.5	17.5
M5	0.5-3.0	7.1	7	8	0.5	18
M5	3.0-5.0	7.1	7	8	0.5	20.5
M6	0.5-3.0	9.1	9	10	0.5	21
M6	3.0-5.0	9.1	9	10	0.5	23.5
M8	0.5-3.0	11.1	11	12	0.5	23.5
M8	3.0-5.5	11.1	11	12	0.5	26.5
M10	1.0-3.5	13.1	13	14.2	0.8	26.5

Flange Head - Knurled Body



STAINLESS STEEL A2

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M3	0.5-2.0	5	4.9	8	0.8	9.8
M4	0.5-2.5	6	5.9	9	1	12
M4	2.5-4.0	6	5.9	9	1	13.5
M5	0.5-3.0	7	6.9	10	1	13
M5	3.0-5.5	7	6.9	10	1	16
M6	0.5-3.0	9	8.9	12	1.5	15.5
M6	3.0-5.5	9	8.9	12	1.5	17.5
M8	0.5-3.0	11	10.9	15	1.5	17.5
M8	3.0-5.5	11	10.9	15	1.5	20
M10	1.0-3.5	13	12.9	17	2	21
M10	3.5-6.0	13	12.9	19	2	24
M12	1.0-4.0	16	15.9	23	2	25

Flange Head - Plain Body



NOTE: Please consider using the popular alternative knurled type.

● **STAINLESS STEEL A2**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-2.0	5	4.9	8	0.8	9.8
M4	0.5-2.5	6	5.9	9	1	12
M4	2.5-4.0	6	5.9	9	1	13.5
M5	0.5-3.0	7	6.9	10	1	13
M5	3.0-4.5	7	6.9	10	1	14.5
M6	0.5-3.0	9	8.9	12	1.5	15.5
M6	3.0-5.0	9	8.9	12	1.5	17.5
M8	0.5-3.0	11	10.9	15	1.5	17.5
M8	3.0-5.5	11	10.9	15	1.5	20

Flange Head - Half Hex Body



The flange head style is suitable for load bearing applications as the larger diameter head reinforces the hole and increases push-out resistance.

● **STAINLESS STEEL A2**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	9	1	12
M4	2.5-4.0	6.1	6	9	1	13.5
M5	0.5-3.0	7.1	7	10	1	13
M5	3.0-4.5	7.1	7	10	1	14.5
M6	0.5-3.0	9.1	9	12	1.5	15.5
M6	3.0-5.0	9.1	9	12	1.5	17.5
M8	0.5-3.0	11.1	11	14.5	1.5	17.5
M8	3.0-5.5	11.1	11	14.5	1.5	20
M10	1.0-3.5	13.1	13	16.5	2	21

Flange Head - Half Hex Body - Closed End



Longer grip version also available, if required please request details.

● **STAINLESS STEEL A2**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	9	1	17
M5	0.5-3.0	7.1	7	10	1	19
M6	0.5-3.0	9.1	9	12	1.5	22.5
M8	0.5-3.0	11.1	11	15	1.5	25
M10	0.8-3.5	13.1	13	17	1.5	30

Flange Head - Closed End




Closed end rivet nuts prevent the ingress of moisture and contamination into a component and are available in both round and hexagon body style. If sealing the nut is critical then a dry under head sealant can be applied. The closed end rivet nuts can also be used to prevent too long a screw being inserted and damaging the part.

● **STAINLESS STEEL A2**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	9	1	17
M5	0.5-3.0	7.1	7	10	1	19
M6	0.5-3.0	9.1	9	12	1.5	22.5
M6	3.0-5.0	9.1	9	12	1.5	25
M8	0.5-3.0	11.1	11	15	1.5	25
M8	3.0-5.5	11.1	11	15	1.5	27.5
M10	1.0-3.5	13.1	13	17	2	28.5

Countersunk Head - Knurled Body



● **STAINLESS STEEL A2**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	1.5-3.5	5	4.9	7.5	1.5	11.5
M4	1.5-4.0	6	5.9	8.5	1.5	12.5
M5	1.5-4.5	7	6.9	9.5	1.5	13.5
M5	4.0-6.5	7	6.9	9.5	1.5	16
M6	1.5-4.5	9	8.9	11.5	1.5	16
M6	4.0-6.5	9	8.9	11.5	1.5	18
M8	1.5-4.5	11	10.9	13.5	1.5	18
M8	4.0-6.5	11	10.9	13.5	1.5	21
M10	2.0-4.5	13	12.9	15.5	1.8	21
M10	4.5-7.5	13	12.9	15.5	1.8	24
M12	2.0-4.5	16	15.9	19	2	24.5
M12	4.5-7.5	16	15.9	19	2	27.5

Countersunk Head - Plain Body



The countersunk head style provides a strong head form and will install flush in a countersunk hole. Suitable for use in material of 1.5mm or greater thickness.

● **STAINLESS STEEL A2**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	1.5-4.0	6	5.9	8.5	1.5	12
M5	1.5-4.5	7	6.9	9.5	1.5	13.5
M6	1.5-4.5	9	8.9	11.5	1.5	16
M8	1.5-4.5	11	10.9	13.5	1.5	18


Countersunk Head - Plain Body - Closed End



● **STAINLESS STEEL A2**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	1.3-3.0	6.1	6	7.8	1	16.1
M4	2.0-3.7	6.1	6	7.8	1	16.8
M5	1.5-3.5	7.1	7	8.8	1	18.5
M5	2.5-4.5	7.1	7	8.8	1	19.5
M6	1.5-3.5	9.1	9	10.8	1	21.9
M6	2.5-4.5	9.1	9	10.8	1	22.9
M6	3.5-5.5	9.1	9	10.8	1	23.9
M8	1.8-4.2	11.1	11	13.8	1.5	26
M8	2.5-5.0	11.1	11	13.8	1.5	26.8
M8	4.0-6.6	11.1	11	13.8	1.5	28.2
M10	2.0-5.5	13.1	13	15.8	1.5	33.4
M10	4.0-7.0	13.1	13	15.8	1.5	34.9

Reduced CSK Head - Plain Body



The reduced countersunk head style rivet nuts offer near flush installation without any extra hole preparation.

ALUMINIUM ALLOY

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	1.0-3.5	6.1	6	7	0.5	12
M5	1.0-3.5	7.1	7	8	0.5	13
M6	1.0-4.0	9.1	9	10	0.5	15.5
M8	1.0-4.0	11.1	11	12	0.7	17
M4	6.73	6.73	9.52	3.17	3.17	3.17

Reduced CSK Head - Knurled Body



ALUMINIUM ALLOY

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-2.5	5	4.9	6	0.6	9.5
M4	0.5-2.0	6	5.9	7	0.6	10.5
M5	0.5-2.0	7	6.9	8	0.6	11.5
M6	0.5-2.5	9	8.9	10	0.6	14
M8	0.5-2.5	11	10.9	12	0.6	15.5
M10	1.0-3.0	13	12.9	14.1	0.7	17.7

Reduced CSK Head - Closed End



Closed end aluminium rivet nuts prevent the ingress of moisture and contamination into a component and are available in all three head styles.

ALUMINIUM ALLOY

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	0.5-3.0	6.1	6	6.9	0.6	16
M5	0.5-3.0	7.1	7	7.9	0.6	18
M6	0.5-3.5	9.1	9	9.9	0.6	21.5

Flange Head



The flange head style is suitable for load bearing applications as the larger diameter head reinforces the hole and increases push-out resistance.

ALUMINIUM ALLOY

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	0.5-2.0	6	5.9	9	0.8	10.5
M5	0.5-3.0	7	6.9	10	1	13
M6	0.5-3.0	9	8.9	13	1.5	16
M8	0.5-3.0	11	10.9	16	1.5	18
M10	1.0-4.0	13	12.9	16.5	1.6	19

Flange Head - Knurled Body



ALUMINIUM ALLOY

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-2.5	5	4.9	7	0.8	10.5
M3	2.5-3.5	5	4.9	7	0.8	11.5
M4	0.5-3.0	6	5.9	9	1	11
M4	3.0-4.5	6	5.9	9	1	14
M5	0.5-2.5	7	6.9	10	1	13
M5	3.0-5.5	7	6.9	10	1	16
M5	5.5-8.0	7	6.9	10	1	19
M6	0.5-2.5	9	8.9	12	1.5	15
M6	3.0-5.5	9	8.9	12	1.5	18.5
M6	5.5-8.0	9	8.9	12	1.5	21
M8	0.5-3.0	11	10.9	15	1.5	17
M8	3.0-5.5	11	10.9	15	1.5	20
M8	5.5-8.0	11	10.9	15	1.5	22.5
M8	8.0-10.5	11	10.9	15	1.5	25
M10	0.5-3.0	12	11.9	16	2	19
M10	3.0-6.0	12	11.9	16	2	24
M10	6.0-9.0	12	11.9	16	2	27
M10	9.0-12.0	12	11.9	16	2	30
M12	1.0-4.0	16	15.9	22	2	25
M12	4.0-7.0	16	15.9	22	2	28
M12	7.0-10.0	16	15.9	22	2	31

Flange Head - Knurled Body - Closed End



ALUMINIUM ALLOY

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	0.5-2.5	5	4.9	7	0.8	15
M3	2.5-3.5	5	4.9	7	0.8	16
M4	0.5-3.0	6	5.9	9	1	16
M4	3.0-4.5	6	5.9	9	1	19
M5	0.5-3.0	7	6.9	10	1	18.5
M5	3.0-5.5	7	6.9	10	1	21.5
M5	5.5-8.0	7	6.9	10	1	24.5
M6	0.5-3.0	9	8.9	12	1.5	21.5
M6	3.0-5.5	9	8.9	12	1.5	24
M6	5.5-8.0	9	8.9	12	1.5	26.5
M8	0.5-3.0	11	10.9	15	1.5	26
M8	3.0-5.5	11	10.9	15	1.5	28.5
M8	5.5-8.0	11	10.9	15	1.5	31
M8	8.0-10.5	11	10.9	15	1.5	33.5
M10	0.5-3.0	12	11.9	16	2	28
M10	3.0-6.0	12	11.9	16	2	33
M10	6.0-9.0	12	11.9	16	2	36
M10	9.0-12.0	12	11.9	16	2	39

Countersunk Head



The countersunk head style provides a strong head form and will install flush in a countersunk hole. Suitable for use in material of 1.5mm or greater thickness.

● **ALUMINIUM ALLOY**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	1.5-3.5	6	5.9	8.5	1.5	11.5
M5	1.5-4.0	7	6.9	9.5	1.5	13
M6	1.5-4.0	9	8.9	11.5	1.5	16
M8	1.5-4.5	11	10.9	13.5	1.5	18.5

Countersunk Head - Knurled Body



● **ALUMINIUM ALLOY**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M3	1.5-3.5	5	4.9	7.5	1.5	11.5
M3	3.5-4.5	5	4.9	7.5	1.5	12.5
M4	1.5-4.0	6	5.9	8.5	1.5	12.5
M4	4.0-5.5	6	5.9	8.5	1.5	15
M5	1.5-4.0	7	6.9	9.5	1.5	13.5
M5	4.0-6.5	7	6.9	9.5	1.5	16
M5	6.5-9.0	7	6.9	9.5	1.5	18.5
M6	1.5-4.0	9	8.9	11.5	1.5	15.5
M6	4.0-6.5	9	8.9	11.5	1.5	18
M6	6.5-9.0	9	8.9	11.5	1.5	20.5
M8	1.5-4.0	11	10.9	13.5	1.5	18.5
M8	4.0-6.5	11	10.9	13.5	1.5	21
M8	6.5-9.0	11	10.9	13.5	1.5	23.5
M10	2.0-4.5	12	11.9	14.5	1.7	21
M10	4.5-7.5	12	11.9	14.5	1.7	24
M10	7.5-10.5	12	11.9	14.5	1.7	27
M12	2.0-4.5	16	15.9	19	1.9	24.5
M12	4.5-7.5	16	15.9	19	1.9	27.5
M12	7.5-10.5	16	15.9	19	1.9	31

Countersunk Head - Closed End



● **ALUMINIUM ALLOY**

Thread Size	Grip Range	Hole Dia.	Body Dia.	Head Dia.	Head Thickness	Overall length
M4	1.5-3.5	6.1	6	9	1.5	16
M4	3.0-5.0	6.1	6	9	1.5	17.5
M5	1.5-4.0	7.1	7	10	1.5	19
M5	3.5-6.0	7.1	7	10	1.5	21
M6	1.5-4.5	9.1	9	12	1.5	23
M6	4.0-6.5	9.1	9	12	1.5	25
M8	1.5-4.5	11.1	11	14	1.5	25.5
M8	4.0-6.5	11.1	11	14	1.5	27.5



QUALITY

- ISO 9001:2015 Certified
- Certificate of Conformity Provided
- Full Traceability
- Manufacturers Test Certificates Available

**Reduced CSK Head
- Knurled Body**



A4 (316) grade stainless steel is the most corrosion resistant grade used for fasteners with an increased percentage content of nickel and added molybdenum. The result is better resistance to aggressive conditions, acids and chlorides found in marine, coastal and some industrial applications.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6	6	7	0.5	11
M5	0.5-3.0	7	7	8	0.5	12
M6	0.5-3.0	9	9	10	0.5	14
M8	0.5-3.0	11	11	12	0.5	16
M10	1.0-3.5	13	13	14.2	0.8	19

**CSK Head
- Plain Body**



STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6	6	7	0.5	11
M5	0.5-3.0	7	7	8	0.5	12
M6	0.5-3.0	9	9	10	0.5	14
M8	0.5-3.0	11	11	12	0.5	16

**Reduced CSK Head
- Half Hex Body**



The reduced countersunk head style offers near flush installation without any extra hole preparation. The halfhexagon body type completely eliminates any chance of the rivet nut rotating in the application.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	7	0.5	11
M5	0.5-3.0	7.1	7	8	0.5	12
M6	0.5-3.0	9.1	9	10	0.5	14.5
M8	0.5-3.0	11.1	11	12	0.5	16
M8	3.0-5.0	11.1	11	12	0.5	18.5
M10	1.0-3.5	13.1	13	14.2	0.7	19

**Reduced CSK Head
- Closed End**



A4 (316) grade stainless steel is the most corrosion resistant grade used for fasteners with an increased percentage content of nickel and added molybdenum. The result is better resistance to aggressive conditions, acids and chlorides found in marine, coastal and some industrial applications.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6	5.9	7	0.5	16
M5	0.5-3.0	7	6.9	8	0.5	18
M6	0.5-3.0	9	8.9	10	0.5	21
M8	0.5-3.0	11	10.9	12	0.5	23.5

**Reduced CSK Head - Half
Hex Body - Closed End**



Closed end rivet nuts prevent the ingress of moisture and contamination into a component and are available in both round and hexagon body style. If sealing the nut is critical then a dry under head sealant can be applied. The closed end rivet nuts can also be used to prevent too long a screw being inserted and damaging the part.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	7	0.5	16
M5	0.5-3.0	7.1	7	8	0.5	18
M6	0.5-3.0	9.1	9	10	0.5	21
M8	0.5-3.0	11.1	11	12	0.5	23.5

Countersunk Head



The countersunk head style provides a strong head form and will install flush in a countersunk hole. Suitable for use in material of 1.5mm or greater thickness.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M5	1.5-4.0	7	6.9	9.5	1.5	13.5
M6	1.5-4.0	9	8.9	11.5	1.5	15.5
M8	1.5-4.0	11	10.9	13.5	1.5	18.5

Flange Head - Knurled Body



The flange head style is suitable for load bearing applications as the larger diameter head reinforces the hole and increases push-out resistance.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M3	0.3-2.0	5	5	8	0.8	9.8
M4	0.3-2.5	6	6	9	1	12
M5	0.3-3.0	7	7	10	1	13
M6	0.5-3.0	9	9	12	1.5	15.5
M8	0.5-3.0	11	11	15	1.5	17.5
M10	1.0-3.5	13	13	17	2	21

Flange Head



STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6	6	9	1	12
M5	0.5-3.0	7	7	10	1	13
M6	0.5-3.0	9	9	12	1.5	15.5
M6	3.0-5.0	9	9	12	1.5	18
M8	0.5-3.0	11	11	15	1.5	17.5

Flange Head - Closed End



A4 (316) grade stainless steel is the most corrosion resistant grade used for fasteners with an increased percentage content of nickel and added molybdenum. The result is better resistance to aggressive conditions, acids and chlorides found in marine, coastal and some industrial applications.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6	6	9	1	17
M5	0.5-3.0	7	7	10	1	19
M6	0.5-3.0	9	9	12	1.5	22.5
M8	0.5-3.0	11	11	15	1.5	25

Flange Head - Half Hex Body



This style of rivet nut is suitable for applications where both high push-out and high torque-out performance are required.

STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	9	1	12
M5	0.5-3.0	7.1	7	10	1	13
M6	0.5-3.0	9.1	9	12	1.5	15.5
M8	0.5-3.0	11.1	11	14.5	1.5	17.5
M10	1.0-3.5	13.1	13	16.5	2	21

Flange Head - Half Hex Body - Closed End



STAINLESS STEEL A4 (316)
extra high corrosion resistance

Thread Size	Grip Range	Hole Dia.	Body Dia. Max	Head Dia.	Head Thickness	Overall length
M4	0.5-2.5	6.1	6	9	1	17
M5	0.5-3.0	7.1	7	10	1	19
M6	0.5-3.0	9.1	9	12	1.5	22.5
M8	0.5-3.0	11.1	11	14.5	1.5	25
M10	1.0-3.5	13.1	13	16.5	2	28.5