

Metric Low Head Cap Screws - Din 7984

Thread	Pitch	Head Dia		Head Hgt		Skt	Skt	Min
Size	(T.P.I)	MIN	MAX	MIN	MAX	A/F	Depth	T.L.
M3	0.50	5.32	5.5	2.16	2.3	2.0	2.0	18
M4	0.70	6.78	7.0	2.62	2.8	2.5	2.3	20
M5	0.80	8.28	8.5	3.32	3.5	3.0	2.7	22
M6	1.00	9.78	10.0	3.70	4.0	4.0	3.0	24
M8	1.25	12.73	13.0	4.64	5.0	5.0	4.2	28
M10	1.50	15.73	16.0	5.64	6.0	7.0	4.8	32
M12	1.75	17.73	18.0	6.57	7.0	8.0	5.3	36
M14	2.00	20.67	21.0	7.57	8.0	10.0	5.5	40
M16	2.00	23.67	24.0	8.57	9.0	12.0	5.5	44
M18	2.50	26.67	27.0	9.57	10.0	12.0	7.5	48
M20	2.50	29.67	30.0	10.48	11.0	14.0	7.5	52
M22	2.50	32.61	33.0	11.48	12.0	14.0	8.0	56
M24	3.00	35.61	36.0	12.48	13.0	17.0	8.0	60
M27	3.00	39.61	40.0	14.48	15.0	17.0	9.0	66

Metric Low Head Cap Screws - Din 6912

Thread	Pitch	Head	Head	Skt	Skt	Pilot	Pilot	Min
Size	(T.P.I)	Hgt	Dia	A/F	Depth	Dia	Depth	T.L.
M4	0.70	2.8	7.0	3.0	1.6	2.0	3.0	20
M5	0.80	3.5	8.5	4.0	2.0	2.5	4.0	22
M6	1.00	4.0	10.	5.0	2.5	3.0	5.0	24
M8	1.25	5.0	13.0	6.0	3.0	4.0	5.5	28
M10	1.50	6.5	16.0	8.0	3.5	5.0	7.5	32
M12	1.75	7.5	18.0	10.0	4.0	6.0	9.0	36
M14	2.00	8.5	21.0	12.0	4.5	7.0	10.0	40
M16	2.00	10.0	24.0	14.0	5.5	8.0	11.5	44
M18	2.50	11.0	27.0	14.0	6.0	8.0	12.5	48
M20	2.50	12.0	30.0	17.0	6.5	10.0	14.0	52
M22	2.50	13.0	33.0	17.0	7.0	10.0	15.0	56
M24	3.00	14.0	36.0	19.0	7.0	12.0	16.0	60
M27	3.00	16.0	40.0	19.0	8.5	12.0	17.0	66

These dimensions are for use as guide purposes only