

Metric Hexagon Full Nuts DIN 934

Thread	Course	Hexagon A/F		A/C	Thickness	
		Min	Max		Min	Max
M1.6	0.35	3.02	3.20	3.41	1.05	1.30
M2	0.4	3.82	4.00	4.32	1.35	1.60
M2.5	0.45	4.82	5.00	5.45	1.75	2.00
M3	0.5	5.32	5.50	6.01	2.15	2.40
M4	0.7	6.78	7.00	7.66	2.90	3.20
M5	0.8	7.78	8.00	8.79	3.70	4.00
M6	1.0	9.78	10.00	11.05	4.70*	5.00*
M7	1.0	10.73	11.00	12.12	5.20	5.50
M8	1.25	12.73	13.00	14.38	6.14*	6.50*
M10	1.5	16.73*	17.00*	18.90*	7.64*	8.00*
M12	1.75	18.67*	19.00*	21.10*	9.64*	10.00*
M14	2.0	21.67*	22.00*	24.49*	10.30*	11.00*
M16	2.0	23.67	24.00	26.75	12.30*	13.00*
M18	2.5	26.16	27.00	29.56	14.30*	15.00*
M20	2.5	29.16	30.00	32.95	14.90*	16.00*
M22	2.5	31.00*	32.00*	35.03*	16.90*	18.00*
M24	3.0	35.00	36.00	39.55	17.70*	19.00*
M27	3.0	40.00	41.00	45.20	20.70*	22.00*
M30	3.5	45.00	46.00	50.85	22.70*	24.00*
M33	3.5	49.00	50.00	55.37	24.70*	26.00*
M36	4.0	53.80	55.00	60.79	27.40*	29.00*
M39	4.0	58.80	60.00	66.44	29.40*	31.00*
M42	4.5	63.10	65.00	71.30	32.40	34.00
M45	4.5	68.10	70.00	76.95	34.40	36.00
M48	5.0	73.10	75.00	82.60	36.40	38.00
M52	5.0	78.10	80.00	88.25	40.40	42.00
M56	5.5	82.80	85.00	93.56	43.40	45.00
M60	5.5	87.80	90.00	99.21	46.40	48.00
M64	6.0	92.80	95.00	104.86	49.10	51.00
M68	6.0	97.80	100.00	110.51	52.10	54.00
M72	6.0	102.80	105.00	116.16	56.10	58.00

\* Indicates there is a different dimension for ISO 4032